

# Building Automated System Cables

## BAS Cable 2P w.Shield

### APPLICATIONS :

- BUILDING SOUND, BROADCAST, AUDIO AND INSTRUMENT
- REMOTE CONTROL OF AUTOMATIC ELECTRICAL EQUIPMENT ex. RECORDING & RELAYING DEVICES LIFT, LIGHT AND AIR CON. SYSTEM VOLTAGE CONTROL SYSTEM OTHER COMMONLY UTILIZED FOR IN PROCESS CONTROL

### PRODUCT DESCRIPTION :

#### CONDUCTOR

- 22 THRU 14 AWG STRANDED TINNED COPPER

#### INSULATION

- COLOR CODED PE INSULATION, BLACK , CLEAR, WHITE, BLUE

#### SHIELDED

- 100% ALUMINUM-MYLAR TAPE SHIELD WITH TINNED COPPER DRAIN WIRE

#### JACKET

- PVC GREY JACKET

#### TEMP.RATING

- -20 TO +75 °C

#### MAX. VOLTAGE

- 300 V RMS



UL file no.E135928

Part No.	No. of Pairs	Nominal Conductor AWG (No./mm.)	Nominal Insulation thickness inch	Nominal Insulation thickness mm.	Drain wire Size	Jacket thick mm.	Nom. OD. mm.
P/N8222	2	22 7/0.254	0.02	0.41	22	0.64	7.5
P/N8220	2	20 10/0.254	0.02	0.41	20	0.71	9.6
P/N8218	2	18 16/0.254	0.02	0.46	20	0.71	10.8
P/N8216	2	16 26/0.254	0.03	0.81	18	0.81	12.5
P/N8214	2	14 42/0.254	0.03	0.81	16	0.89	14.2

