

Self Support Crane Control Cable

PVC insulated, PVC jacket 600V-Single Sling

- Conductor:** Fine stranded copper conductor
Insulation : Color coded PVC insulation
 Core cabled under fabric tape
Jacket: PVC jacket with self supporting steel wire
Rated: Temp. 75°C. Voltage 600 V.
 Pass UL VW-1 and CSA FT1 vertical flame test
Application: For vertical switch control of crane or electrical equipment



Single Sling

Part Number	Number Of Conductor	Conductor		Insulation		Jacket		Self Support Wire (mm.)	Jacket Color
		mm ²	No/mm.	Nom. Thickness (mm.)	Nominal O.D. (mm.)	Material	Nominal O.D. (mm.)		
HECR 1.25	5	1.25	50/0.18	0.80	3.0	PVC	11.7 x 19.2	3.0	Black
	8	1.25	50/0.18	0.80	3.0	PVC	15.5 x 23.0	3.0	Black
	10	1.25	50/0.18	0.80	3.0	PVC	16.0 x 23.5	3.0	Black
	14	1.25	50/0.18	0.80	3.0	PVC	17.3 x 24.8	3.0	Black
	20	1.25	50/0.18	0.80	3.0	PVC	21.0 x 28.5	3.0	Black

